NSN 5985-01-478-3273

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-478-3273

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Overall Length:
2.500 inches
Overall Diameter:
0.820 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
2.00
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Coaxial Connector Series Designation:
_
N
N Rf Signal Attenuation In Decibels:
N Rf Signal Attenuation In Decibels: 20.0
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method:
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity:
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life:
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a
N Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a
Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a Unit Of Measure:
Rf Signal Attenuation In Decibels: 20.0 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: