

View Online at <https://aerobasegroup.com/nsn/5985-01-482-3577>

**Application Design:**

Transmission line

**Body Style:**

Irregular

**Overall Length:**

3.195 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.180 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.250 inches

**Overall Height:**

1.600 inches

**Overall Width:**

1.750 inches

**End Application:**

Early warning radar

**Voltage Standing Wave Ratio:**

1.51

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

3.0 kilowatts peak

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.05

**Overall Attenuation Range In Decibels:**

+0.0/+20.0

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

2 threaded hole

**Frequency Range:**

Between 2.000 gigahertz and 4.000 gigahertz

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 knob and 1 slotted screw

**Mounting Facility Pattern:**

Two position in-line

**Mounting Facility Screw Thread Diameter:**

0.150 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Special Features:**

Panel mount

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0