NSN 5985-01-484-6694

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-484-6694

Body Style:

Coaxial type

Overall Length:

Between 1.600 inches and 1.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.870 inches and 0.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.620 inches and 1.630 inches

Overall Height:

Between 2.150 inches and 2.350 inches

Overall Width:

Between 0.470 inches and 0.530 inches

Voltage Standing Wave Ratio:

1.60

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average and 10.0 watts peak

Mounting Facility Screw Thread Series Designator:

Unc

0.5

Insertion Loss At Minimum Attenuation In Maximum Decibels:

Overall Attenuation Range In Decibels:

+0.0/+20.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 8.000 gigahertz and 12.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-2.50/+2.50

Mounting Thread Quantity:

56 per inch

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.086 inches

Mounting Thread Tolerance Class:

2b internal

Terminal Type And Quantity:

2 connector, coaxial, female

NSN 5985-01-484-6694

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0