## NSN 5985-01-491-2925



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-491-2925 **Application Design:** Transmission line **Body Material: Brass Body Style:** Err-090 **Body Surface Treatment:** Nickel plated **Overall Length:** 2.600 inches **Overall Diameter:** 0.640 inches **Operating Tempurature Range:** -20.0/+85.0 degrees celsius **End Application:** Radar threat emiter an/mst-t1; next assembly 3050744, 3050780, 3050781 and 3051173 **Voltage Standing Wave Ratio:** 1.06 and 1.22 and 1.40 **Input Impedance Rating In Ohms:** 75.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 0.25 watts average Rf Signal Attenuation In Decibels: 5.7 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+2000.0 megahertz **Connection Type Per Function:** Male input and female output **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 2000.000 megahertz Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5985-01-491-2925

Fixed Attenuator - Page 2 of 2



Fiig:

A20000