## NSN 5985-01-493-8471

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-493-8471

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
0.860 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.12
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Coaxial Connector Series Designation: Sma
_
Sma
Sma Power Rating:
Sma Power Rating: 2.0 watts average
Sma Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels:
Sma Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0
Sma  Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 22.0  Attenuation Accuracy In Decibels:
Sma Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00
Sma  Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 22.0  Attenuation Accuracy In Decibels: -1.00/+1.00  Terminal Type And Quantity:
Sma  Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 22.0  Attenuation Accuracy In Decibels: -1.00/+1.00  Terminal Type And Quantity: 2 connector
Sma  Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 22.0  Attenuation Accuracy In Decibels: -1.00/+1.00  Terminal Type And Quantity: 2 connector  Frequency Range:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a Unit Of Measure:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 22.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: