NSN 5985-01-494-5622

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-494-5622

Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Overall Length:
Between 1.330 inches and 1.390 inches
Overall Diameter:
0.500 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
Cv-405 (v) 8/usc-38(v) , mpw apcu, sub
Voltage Standing Wave Ratio:
1.15 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 250.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +8.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-494-5622

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000