

View Online at <https://aerobasegroup.com/nsn/5985-01-496-9784>

Application Design:

Transmission line

Body Material:

Metal

Body Style:

Err-090

Overall Length:

1.240 inches

Overall Diameter:

Between 0.350 inches and 0.385 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

As4494a/spq9b; as-4499a/spq antenna

Voltage Standing Wave Ratio:

1.15 and 1.20 and 1.25 and 1.35

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

28.0

Attenuation Accuracy In Decibels:

-0.70/+0.70

Connection Type Per Function:

Male input and female output

Unpackaged Unit Weight:

0.500 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Special Features:

Vswr frequency ranges are 0.0 to 4.0 ghz, 4.0 to 8.0 ghz, 8.0 to 12.4 ghz, and 12.4 to 18.0 ghz

Test Data Document:

81349-mil-a3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-a-3933/16-55 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000