

View Online at <https://aerobasegroup.com/nsn/5985-01-497-5539>

Body Style:

Rectangular

Overall Length:

2.150 inches

Overall Height:

1.630 inches

Overall Width:

0.520 inches

Frequency Rating:

0.0 gigahertz single frequency operating and 8.4 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.177 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.375 inches single mounting facility pattern

End Application:

Oe-562/usc-3 (v) , antenna group, next assembly g745287 and g608294

Voltage Standing Wave Ratio:

1.30 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

150.0 watts peak single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.110 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Latching

Pole Quantity:

2

Throw Quantity:

1

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum connecto (s)

Unpackaged Unit Weight:

3.000 ounces

Terminal Type And Quantity:

1 connector, receptacle and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0