

View Online at <https://aerobasegroup.com/nsn/5985-01-497-5553>

Thread Class:

2b mounting facility hole

Body Style:

Rectangular

Overall Length:

4.450 inches

Overall Height:

3.180 inches

Overall Width:

2.250 inches

Frequency Rating:

7.05 gigahertz single frequency operating and 10.00 gigahertz single frequency operating

Switch Type:

Transfer

Distance Between Mounting Facility Centers:

1.474 inches 2nd mounting facility pattern

End Application:

Oe-562/usc-3 (v) , antenna group, next assembly g608299 and g745287

Voltage Standing Wave Ratio:

1.10 single

Insertion Loss In Decibels:

0.05 single

Rf Power Handling Capability:

202.0 kilowatts peak single

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Motor

Actuator Current Type And Rating In Amps:

1.75 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

120.0 milliseconds

Waveguide Flange Type:

Cover

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 threaded hole

Thread Size:

0.164 inches mounting facility hole

Mounting Facility Pattern:

Two position in-line 2nd mounting facility pattern

Flange Connecting Facility And Quantity:

12 threaded hole

Material:

Aluminum flang (s)

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0