NSN 5985-01-498-2715

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-498-2715 **Application Design:** Transmission line **Body Material: Brass Body Style:** Err-090 **Body Surface Treatment:** Nickel plated **Overall Length:** 2.600 inches **Overall Diameter:** 0.640 inches **Operating Tempurature Range:** -20.0/+85.0 degrees celsius **End Application:** An/bsr-1, w/fc no.1, subsurface receiver suite (ssrs); next assembly 3050744, 3050780, 3050781, 3051173 used on an/mst-t (v) **Voltage Standing Wave Ratio:** 1.06 and 1.22 and 1.40 **Input Impedance Rating In Ohms:** 75.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 0.25 watts average Rf Signal Attenuation In Decibels: 5.7 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+2000.0 megahertz **Connection Type Per Function:** Female input and male output **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 2000.000 megahertz Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-01-498-2715

Fixed Attenuator - Page 2 of 2



Fiig:

A20000