# NSN 5985-01-498-2977

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-498-2977

## Application Design:

Transmission line

#### **Body Material:**

Steel, stainless

## Body Style:

Err-090

#### **Terminal Material:**

Steel, stainless

#### **Terminal Surface Treatment:**

Passivated

#### **Body Surface Treatment:**

Passivated

#### **Overall Length:**

Between 0.835 inches and 0.875 inches

#### **Overall Diameter:**

0.280 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.15 and 1.40

### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

2.0 watts average

#### **Rf Signal Attenuation In Decibels:**

1.0

## Voltage Standing Wave Ratio Frequency Range:

+4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

## Attenuation Accuracy In Decibels:

-0.30/+0.30

## Unpackaged Unit Weight:

4.100 grams

## Mounting Method:

Connector

## Terminal Type And Quantity:

2 connector

## Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

# NSN 5985-01-498-2977

Fixed Attenuator - Page 2 of 2



#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material:**

Gold

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A20000