

View Online at <https://aerobasegroup.com/nsn/5985-01-498-9690>

Body Style:

Rectangular

Overall Length:

Between 2.040 inches and 2.080 inches

Overall Height:

2.630 inches

Overall Width:

Between 0.540 inches and 0.580 inches

Frequency Rating:

0.0 gigahertz single frequency operating and 18.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.120 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.320 inches single mounting facility pattern

End Application:

Ueu sra otps, next assembly 802025205100-1 used on on-517/usm-63 (v)

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.40 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Solid state

Actuator Current Type And Rating In Amps:

0.15 dc

Actuator Voltage In Volts:

12.0

Switch Operation Sequence:

Breaks before makes

Switch Return Mechanism Type:

Latching

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Terminal Type And Quantity:

3 receptacle, coaxial and 3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0