NSN 5985-01-504-2566

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-504-2566

New Online at https://defobasegroup.com/nsi//3503-01-304-2300	
Application Design:	
Transmission line	
Body Style:	
Coaxial type	
Overall Length:	
2.760 inches	
Overall Height:	
0.560 inches	
Overall Width:	
2.500 inches	
End Application:	
M3p reu-m; wsd: radar threat emiter an/mst-t1	
Voltage Standing Wave Ratio:	
1.50	
Coaxial Connector Series Designation:	
Sma	
Power Rating:	
5.0 watts average and 3.0 kilowatts peak	
Mounting Facility Screw Thread Series Designator:	
Unc	
Insertion Loss At Minimum Attenuation In Maximum Decibels:	
0.5	
Attenuation Variation Method:	
Continuous	
Mounting Facility Type And Quantity:	
6 threaded hole	
Frequency Range:	
Between 14.000 gigahertz and 14.500 gigahertz	
Mounting Thread Quantity:	
40 per inch	
Adjustment Device Type And Quantity:	
1 knob w/dial	
Mounting Facility Screw Thread Diameter:	
0.112 inches	
Special Features:	
Attenuation: 20 db min.	
Terminal Type And Quantity:	
2 connector, coaxial, female	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5985-01-504-2566

Variable Attenuator - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

