## NSN 5985-01-504-2566

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-504-2566

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.760 inches
Overall Height:
0.560 inches
Overall Width:
2.500 inches
End Application:
M3p reu-m; wsd: radar threat emiter an/mst-t1
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average and 3.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
6 threaded hole
Frequency Range:
Between 14.000 gigahertz and 14.500 gigahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 knob w/dial
Mounting Facility Screw Thread Diameter:
0.112 inches
Special Features:
Attenuation: 20 db min.
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
144

--

## NSN 5985-01-504-2566

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0