NSN 5985-01-504-8635

Electrical Dummy Load - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-504-8635

Ambient Tempurature In Des Coleius At Full Deted Deurer
Ambient Tempurature In Deg Celsius At Full Rated Power:
-55.0 and 125.0
Overall Length:
1.510 inches
Impedance Rating In Ohms:
50.0
Overall Diameter:
0.380 inches
Frequency Range Rating:
+0.030/+12.400 gigahertz
End Application:
Rd-677/usg-2 ec14 recorder-reproducer, digital data
Voltage Standing Wave Ratio:
1.10
Coaxial Connector Series Designation:
N .
Connector End Design:
Male
Power Rating:
1.000 watts average and 0.500 kilowatts peak
Voltage Standing Wave Ratio Frequency Range:
+0.030/+12.400 gigahertz
Termination Type:
Connection coaxial
Operating Position:
All positions
Cooling Method:
Self-cooled
Special Features:
Materials: body and connector: corrosion-resistant steel; finish: nickel plated; contact pin and socket: beryllium copper
Style Designator:
Coaxial mounted
Test Data Document:
81349-mil-d-39030 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-d-39030/6 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 5985-01-504-8635

Electrical Dummy Load - Page 2 of 2



Fiig:

A19800