

View Online at <https://aerobasegroup.com/nsn/5985-01-508-9928>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

End Application:

Ab-1383a/bps-1 (v) , mast assembly; wsd: seawolf class ssn

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches second flange and 0.904 inches second flange

Flange Inside Height:

0.396 inches second flange and 0.404 inches second flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

Between 11.940 inches and 12.060 inches

Specified Frequency:

Between 8.2 gigahertz and 12.4 gigahertz

Special Features:

Max twist: 95 deg/ft

Flexibility:

Flexible single tubing segment

Material:

Copper alloy all flange

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0