4 threaded hole

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-509-6962

| view Online at https://aeiobasegioup.com/hsn/5365-01-503-6362 |
|--|
| Body Style: |
| Rectangular |
| Overall Length: |
| 3.580 inches |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 2.000 inches |
| Frequency Rating: |
| 30.0 megahertz single frequency operating and 400.0 megahertz single frequency operating |
| Switch Type: |
| Transfer |
| Distance Between Mounting Facility Centers: |
| 1.625 inches 2nd mounting facility pattern |
| End Application: |
| Misc command x surveillance lcac 0025 |
| Voltage Standing Wave Ratio: |
| 1.30 single |
| Insertion Loss In Decibels: |
| 0.30 single |
| Coaxial Connector Series Designation: |
| Tnc |
| Connector End Design: |
| Female |
| Minimum Crosstalk Rating In Decibels: |
| 60.0 single |
| Actuator Operating Method: |
| Solid state |
| Actuator Current Type And Rating In Amps: |
| 1.0 dc |
| Actuator Voltage In Volts: |
| 24.0 |
| Switch Operation Sequence: |
| Makes before breaks |
| Switching Time: |
| 20.0 milliseconds |
| Switch Return Mechanism Type: |
| Latching |
| Coupling Position Quantity: |
| 4 |
| Mounting Facility Type And Quantity: |
| |

Radio Frequency Transmission Line Switch - Page 2 of 2



Mounting Facility Pattern:

Two position in-line 1st mounting facility pattern

Terminal Type And Quantity:

4 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A158a0