NSN 5985-01-513-4624

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-513-4624

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

End Application:

Next assembly 43140-00364-1 used on mk-2905/spn-35c, module kit, maint assistance; wsd: an/spn-42t-3, 42t-4, & an/spn-4 (v) 1

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.255 inches second flange and 1.258 inches second flange

Flange Inside Height:

0.630 inches second flange and 0.633 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility and 0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.03

Insertion Loss In Decibels:

0.027

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

NSN 5985-01-513-4624

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Length: 11.500 inches **Specified Frequency:** Between 7.05 gigahertz and 10.00 gigahertz Flexibility: Flexible single tubing segment Material: Copper single tubing segment **Precious Material And Location:** Internal surfaces silver **Precious Material:** Silver **Surface Treatment:** Silver single tubing segment inside surfaces Style Designator: Straight type **Thread Series Designator:** Unc first flange single connection facility Shelf Life: N/a Unit Of Measure: **Demilitarization:**

Yes - demil/mli

Fiig:

A073a0