

View Online at <https://aerobasegroup.com/nsn/5985-01-516-4869>

Application Design:

Transmission line

Body Material:

Any acceptable

Body Style:

Rectangular, terminal/terminals on opposite surfaces

Body Surface Treatment:

Any acceptable

Overall Length:

6.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.068 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.782 inches

Overall Height:

1.062 inches

Overall Width:

1.062 inches

Mounting Hole/stud Quantity:

4

End Application:

Signal processor group, aegis

Voltage Standing Wave Ratio:

1.40

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

N

Power Rating:

1.0 watts average

Rf Signal Attenuation In Decibels:

82.5

Attenuation Accuracy Reference Frequency:

0.3 gigahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Connection Type Per Function:

Female input and female output

Mounting Method:

Threaded hole

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

Special Features:

Mfg name: toggle switch attenuator; mounting holes, 4 pl's 6-32 x .380 deep; insertion loss: 1.2 db max; nine attenuation steps: 0.5, 1, 2, 3, 6, 10, 20, 20, 20db

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000