

View Online at <https://aerobasegroup.com/nsn/5985-01-518-8594>

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

Err-090

Body Surface Treatment:

Passivated

Overall Length:

Between 0.960 inches and 1.020 inches

Overall Diameter:

0.280 inches

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

561620 (53711) , phot mast, sensor unit

Voltage Standing Wave Ratio:

1.15 and 1.35

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 250.0 watts peak

Rf Signal Attenuation In Decibels:

30.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +12.4/+18.0 gigahertz

Attenuation Accuracy In Decibels:

-0.75/+0.75

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Special Features:

Conductors: gold plated beryllium copper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000