## NSN 5985-01-519-1359

View Online at https://aerobasegroup.com/nsn/5985-01-519-1359

Fixed Attenuator - Page 1 of 2



**Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 1.850 inches **Overall Diameter:** 0.313 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** Rq-4a **Voltage Standing Wave Ratio:** 1.15 and 1.25 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 4.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+12.4 gigahertz **Attenuation Accuracy Reference Frequency:** 12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.75/+0.75 **Unpackaged Unit Weight:** 0.230 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector **Special Features:** Fixed coaxial attenuator ruggedized sma connector dc to 12.4 ghz.

## NSN 5985-01-519-1359

Fixed Attenuator - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000