

View Online at <https://aerobasegroup.com/nsn/5985-01-527-7921>

**Furnished Items:**

Base and mounting hardware and pedestal and plate and reflector and storage case

**Environmental Protection:**

Humidity proof and shock resistant and vibration resistant and weather resistant

**Operating Temperature Range:**

-5.0/+122.0 degrees fahrenheit

**Beam Scanning Method:**

Tilting single antenna element and rotating single antenna element

**Features Provided:**

Adjustable and transportable

**Special Features:**

Part name assigned by controlling agency - 2.4 meter sf c, x, ku-band, flyaway antenna; azimuth travel plus or minus 360.0 degrees coarse and plus or minus 15.0 degrees fine adjustment; elevation travel plus or minus 95.0 degrees linear polarization only; reflector material is carbon fibre composition color is white; pedestal structure material aluminum; positioner assembly is powder coated grey color; system includes 9 reflector panels, pedestal assembly, feed mounting plate, feed outrigger booms, backspines, and assembly hardware; with ballast can operate in winds of 30.0 miles per hour with gusts to 45.0 mph; using tie downs rated to survive winds of 60.0 mph. With gusts to 75.0 mph; feeds are not included

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A074a0