

View Online at <https://aerobasegroup.com/nsn/5985-01-528-6364>

Body Style:

Rectangular

Overall Length:

Between 2.970 inches and 3.030 inches

Overall Height:

2.280 inches

Overall Width:

0.600 inches

Frequency Rating:

20.0 megahertz single frequency operating and 500.0 megahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.093 inches

Switch Type:

Nontransfer

Longest Vertical Distance Between Mounting Centers:

2.836 inches single mounting facility pattern

Shortest Vertical Distance Between Mounting Centers:

1.586 inches single mounting facility pattern

Operating Temperature Range:

-46.0/+85.0 degrees celsius

End Application:

E/i r-2199/sps-4 (v) , receiver, radar; wsd: nimitz class cvn

Voltage Standing Wave Ratio:

1.25 single

Insertion Loss In Decibels:

1.00 single

Maximum Operating Altitude Rating:

10000.0 feet

Minimum Crosstalk Rating In Decibels:

85.0 single

Actuator Operating Method:

Solid state

Pole Quantity:

1

Throw Quantity:

4

Coupling Position Quantity:

5

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Special Features:

Impedance: 50 ohms; switching time: 0.5 microseconds max; dc bias control current: 175 mamps max

Material:

Aluminum alloy 6063 body

Terminal Type And Quantity:

5 connector, receptacle and 6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0