NSN 5985-01-532-1870

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-532-1870

Cross	Secti	onal	Shape:
U U 3 3	OCCL	ullai	Juane.

Internal, rectangular external, rectangular

End Application:

Oa-9233a/g

Tubing Wall Construction Style:

Seamless second tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

17.0 single tubing segment

Flange Inside Width:

1.372 inches all flanges

Flange Inside Height:

0.872 inches all flanges

Flange Outside Width:

2.690 inches all flanges

Flange Outside Height:

1.940 inches all flanges

Flange Connecting Hole Diameter:

0.194 inches all flanges all connection facilities and 0.198 inches all flanges all connection facilities

Maximum Operating Pressure:

5.0 pounds per square inch gage

Waveguide Longer Offset Distance:

6.360 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Contact type all flanges

Product Name:

Waveguide, receive, vanized

Flexibility:

Flexible single tubing segment

Style Designator:

Bend type

Supplementary Features:

Bend radius: 1.00. Power handling: 500 watts cw.

Specification Data:

81349 - mil-w-287/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5985-01-532-1870

Waveguide Assembly - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A073a0