NSN 5985-01-532-4123

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-532-4123

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Oa-9233a/g

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.372 inches all flanges

Flange Inside Height:

0.622 inches all flanges

Flange Outside Width:

2.690 inches all flanges

Flange Outside Height:

1.940 inches all flanges

Flange Connecting Hole Diameter:

0.194 inches all flanges all connection facilities and 0.198 inches all flanges all connection facilities

Insertion Loss In Decibels:

2.20

Maximum Operating Pressure:

5.0 pounds per square inch gage

Waveguide Outside Width:

1.500 inches

Waveguide Inside Width:

1.372 inches

Waveguide Inside Height:

0.622 inches

Waveguide Outside Height:

0.750 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Contact type all flanges

Waveguide Length:

58.000 inches

Product Name:

Waveguide, receive, vanized

Specified Frequency:

Between 5.8 gigahertz and 8.2 gigahertz

Flexibility:

Rigid single tubing segment

NSN 5985-01-532-4123

Waveguide Assembly - Page 2 of 2



Material:

Aluminum alloy 6061 single tubing segment

Style Designator:

Straight type

Supplementary Features:

Power handling: 8000 watts cw

Specification Data:

81349 - mil-w-85/1-066 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0