

View Online at <https://aerobasegroup.com/nsn/5985-01-532-7433>

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Ot-20 (v) /g, transmitter group; next assembly a3273555

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.372 inches all flanges

Flange Inside Height:

0.622 inches all flanges

Flange Outside Width:

2.690 inches all flanges

Flange Outside Height:

1.940 inches all flanges

Flange Depth:

0.500 inches all flanges

Flange Connecting Hole Diameter:

0.196 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

1.508 inches

Waveguide Inside Width:

1.372 inches

Waveguide Inside Height:

0.622 inches

Waveguide Outside Height:

0.758 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Waveguide First Leg Length:

3.380 inches

Waveguide Fifth Leg Length:

9.500 inches

Flange Style:

Contact type all flanges

Waveguide Length:

52.770 inches

Waveguide Second Leg Length:

2.900 inches

Waveguide Third Leg Length:

38.320 inches

Waveguide Fourth Leg Length:

2.210 inches

Product Name:

Waveguide assembly, w901

Specified Frequency:

Between 7.9 gigahertz and 8.4 gigahertz

Flexibility:

Rigid all tubing segment

Material:

Any acceptable all tubing segment and flange

Surface Treatment:

Any acceptable all tubing segment and flange all surfaces

Style Designator:

Four bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0