

View Online at <https://aerobasegroup.com/nsn/5985-01-532-8898>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**End Application:**

Ot-20 (v) /g, transmitter group; next assembly a3273555, a3273573

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.122 inches all flanges

**Flange Inside Height:**

0.497 inches all flanges

**Flange Outside Width:**

2.500 inches all flanges

**Flange Outside Height:**

1.750 inches all flanges

**Flange Depth:**

0.500 inches all flanges

**Flange Connecting Hole Diameter:**

0.169 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.05

**Waveguide Outside Width:**

1.258 inches

**Waveguide Inside Width:**

1.122 inches

**Waveguide Inside Height:**

0.497 inches

**Waveguide Outside Height:**

0.633 inches

**Flange Connecting Facility And Quantity:**

8 unthreaded hole all flanges all connection facilities

**Waveguide First Leg Length:**

3.630 inches

**Flange Style:**

Contact type all flanges

**Waveguide Length:**

8.940 inches

**Waveguide Second Leg Length:**

6.310 inches

**Waveguide Third Leg Length:**

7.000 inches

**Waveguide Fourth Leg Length:**

2.630 inches

**Product Name:**

Waveguide assembly, w907

**Specified Frequency:**

Between 7.9 gigahertz and 8.4 gigahertz

**Flexibility:**

Rigid single tubing segment

**Material:**

Any acceptable all tubing segment and flange

**Surface Treatment:**

Any acceptable all tubing segment and flange all surfaces

**Style Designator:**

Three bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0