## NSN 5985-01-532-9620

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-532-9620

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

### **End Application:**

Ot-20 (v) /g, transmitter group; next assembly a3273555, a3273573

## **Tubing Wall Construction Style:**

Seamless all tubing segment

Flange Quantity:

2

#### Flange Inside Width:

1.122 inches all flanges

#### Flange Inside Height:

0.497 inches all flanges

#### Flange Outside Width:

2.500 inches all flanges

#### Flange Outside Height:

1.750 inches all flanges

## Flange Depth:

0.500 inches all flanges

## Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities

## **Voltage Standing Wave Ratio:**

1.05

## **Waveguide Outside Width:**

1.258 inches

## Waveguide Inside Width:

1.122 inches

## **Waveguide Inside Height:**

0.497 inches

#### **Waveguide Outside Height:**

0.633 inches

## Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

## Flange Style:

Contact type all flanges

#### **Product Name:**

Waveguide assembly, w905

## **Specified Frequency:**

Between 7.9 gigahertz and 8.4 gigahertz

## **Special Features:**

Two bend type, dimensions: 1st leg 5.44 in., 2nd leg 4.88 in., 3rd leg 9.88 in.

#### Flexibility:

Rigid all tubing segment

# NSN 5985-01-532-9620

Waveguide Assembly - Page 2 of 2



	er	

Any acceptable all tubing segment and flange

**Surface Treatment:** 

Any acceptable all tubing segment and flange all surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A073a0