

View Online at <https://aerobasegroup.com/nsn/5985-01-533-6132>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**End Application:**

Oa-9233a/g, operations group van

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

1

**Flange Inside Width:**

1.122 inches single flange

**Flange Inside Height:**

0.497 inches single flange

**Flange Outside Width:**

2.500 inches single flange

**Flange Outside Height:**

1.750 inches single flange

**Flange Depth:**

0.500 inches single flange

**Flange Connecting Hole Diameter:**

0.169 inches single flange all connection facilities

**Voltage Standing Wave Ratio:**

1.20

**Insertion Loss In Decibels:**

0.30

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

N

**Connector End Design:**

Female

**Adapter Length:**

1.740 inches

**Adapter Height:**

1.940 inches

**Maximum Operating Pressure:**

15.0 pounds per square inch gage

**Waveguide Outside Width:**

1.250 inches

**Waveguide Inside Width:**

1.122 inches

**Waveguide Inside Height:**

0.497 inches

**Waveguide Outside Height:**

0.625 inches

**Flange Connecting Facility And Quantity:**

8 unthreaded hole single flange all connection facilities

**Flange Style:**

Contact type single flange

**Adapterheight:**

2.490 inches

**Adapterwidth:**

2.690 inches

**Product Name:**

Adapter, isolator, waveguide-coax

**Special Features:**

Freq. Range: 7.9-8.4ghz; isolation: 20db min; input power rating: 1w min; termination: 1w avg, 100w peak; connector: corrosion resistant steel, finish: passivated

**Material:**

Copper single flange

**Style Designator:**

Waveguide to coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0