NSN 5985-01-535-2439

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-535-2439

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
2.070 inches
Overall Diameter:
0.560 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
Joint services electronic combat tester an/usm-670
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 250.0 watts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 gigahertz and 18.000 gigahertz
Shelf Life:
N/a
Unit Of Measure:
<u></u>

--

NSN 5985-01-535-2439

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000