## NSN 5985-01-535-4865

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-535-4865 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Terminal Material:** Beryllium copper **Terminal Surface Treatment:** Gold plated, mil-g-45204, type 2, class 1 **Body Surface Treatment:** Passivated, qq-p-35 **Overall Length:** 0.750 millimeters **Overall Diameter:** 0.312 millimeters **Operating Tempurature Range:** -55.0/+150.0 degrees celsius **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Rf Signal Attenuation In Decibels:** 2.0 **Attenuation Accuracy Reference Frequency:** 8.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 gigahertz and 8.000 gigahertz Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5985-01-535-4865

Fixed Attenuator - Page 2 of 2



Fiig:

A20000