

View Online at <https://aerobasegroup.com/nsn/5985-01-537-5850>

Application Design:

Printed circuit board

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.422 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.750 inches

Coaxial Connector Series Designation:

Bnc

Power Rating:

1.0 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.2

Overall Attenuation Range In Decibels:

+0.0/+82.5

Attenuation Per Step In Decibels:

0.5 and 1.0 and 2.0 and 3.0 and 6.0 and 10.0 and 20.0

Mounting Facility Type And Quantity:

1 connector

Frequency Range:

Between 1.000 gigahertz and 750.000 kilohertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.50

Segment Attenuation Range In Decibels:

-0.20/+0.30

Segment Attenuation Accuracy In Decibels:

-1.00/+1.50

Impedance Rating In Ohms:

50.0 input

Terminal Type And Quantity:

2 connector, coaxial, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0