## NSN 5985-01-538-6244

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-538-6244 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 3.490 inches **Overall Diameter:** 1.650 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** Aegis system level apl, ddg91&up; mk7mod20, ddg103t112, misc conn group (combined); wsd: arleigh burke class ddg **Voltage Standing Wave Ratio:** 1.20 and 1.30 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 25.0 watts average **Rf Signal Attenuation In Decibels: Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+18.0 gigahertz **Connection Type Per Function:** Female output and male input **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5985-01-538-6244

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000