

View Online at <https://aerobasegroup.com/nsn/5985-01-547-8750>

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Oe-170 (v) 1-4/fsc, antenna, next assembly a3193614

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.368 inches all flanges and 1.376 inches all flanges

Flange Inside Height:

0.618 inches all flanges and 0.626 inches all flanges

Flange Outside Width:

2.670 inches all flanges and 2.710 inches all flanges

Flange Outside Height:

1.920 inches all flanges and 1.960 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Flange Connecting Hole Diameter:

0.196 inches all flanges all connection facilities and 0.200 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

Waveguide Inside Width:

Between 1.368 inches and 1.376 inches

Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

Waveguide Outside Height:

Between 0.746 inches and 0.754 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Contact type all flanges

Waveguide Center To Center Distance:

14.190 inches

Waveguide Height:

4.140 inches

Specified Frequency:

Between 7.25 gigahertz and 7.75 gigahertz

Special Features:

Waveguide assembly w14 (m85/1-063), flange, wg (5.85-8.20ghz) (m3922/52-039)

Flexibility:

Rigid all tubing segment

Material:

Copper alloy all tubing segment and flange

Style Designator:

Double bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0