

View Online at <https://aerobasegroup.com/nsn/5985-01-562-3273>

Application Design:

Transmission line

Body Style:

Irregular

Overall Length:

5.057 inches

Overall Height:

1.500 inches

Overall Width:

1.823 inches

End Application:

An/gsc-7 (v) 1, isil, used on ka-stars

Voltage Standing Wave Ratio:

1.30 and 1.40 and 1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.5

Overall Attenuation Range In Decibels:

+0.0/+30.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

3

Attenuation Per Step In Decibels:

1.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 0.000 gigahertz and 3.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.00

Adjustment Device Type And Quantity:

2 knob

Mounting Facility Pattern:

Four position diamond

Impedance Rating In Ohms:

50.0 input-output

Product Name:

Dual concentric rotary step attenuator 0-30db (trilithic)

Special Features:

Housing-aluminum and zinc, knob included

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0