

View Online at <https://aerobasegroup.com/nsn/5985-01-564-6686>

Body Style:

Rectangular

Overall Length:

2.750 inches

Overall Height:

2.650 inches

Overall Width:

0.900 inches

Frequency Rating:

1.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.140 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.880 inches single mounting facility pattern and 2.500 inches single mounting facility pattern

Longest Horizontal Distance Between Mounting Centers:

2.500 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.880 inches single mounting facility pattern

Intermediate Horizontal Distance Between Mounting Centers:

1.760 inches single mounting facility pattern

End Application:

Rf switching applications

Rf Power Handling Capability:

1000.0 watts average single

Actuator Operating Method:

Solid state

Actuator Current Type And Rating In Amps:

0.1 dc

Actuator Voltage In Volts:

28.0

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position trapezoid single mounting facility pattern

Product Name:

Spdt switch

Special Features:

Spdt failsafe switch, rf connectors type n; terminals power connector/fast disconnect; freq 0-dc-1ghz; 28vdc; standard mounting holes; polarity not relevant to application for switches with logic

Material:

Aluminum alloy body and plastic body

Special Test Features:

Designed to meet mil-s-3928

Terminal Type And Quantity:

3 quick disconnect, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0