NSN 5985-01-564-6815

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-564-6815

Brass Body Style: Err-090 Body Surface Treatment: Nickel plated Overall Length: Between 1.890 inches and 1.990 inches Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Err-090 Body Surface Treatment: Nickel plated Overall Length: Between 1.890 inches and 1.990 inches Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Body Surface Treatment: Nickel plated Overall Length: Between 1.890 inches and 1.990 inches Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Nickel plated Overall Length: Between 1.890 inches and 1.990 inches Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Overall Length: Between 1.890 inches and 1.990 inches Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Between 1.890 inches and 1.990 inches Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Overall Diameter: 0.620 inches Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Operating Tempurature Range: -45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
-45.0/+100.0 degrees celsius End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
End Application: An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
An/gsc-7 (v) 1, isil Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Voltage Standing Wave Ratio: 1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
1.00 and 1.10 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
50.0 Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Coaxial Connector Series Designation: Bnc Power Rating: 1.0 watts peak							
Bnc Power Rating: 1.0 watts peak							
Power Rating: 1.0 watts peak							
1.0 watts peak							
•							
Rf Signal Attenuation In Decibels:							
5.0							
Attenuation Accuracy In Decibels:							
-0.50/+0.50							
Connection Type Per Function:							
Female input and male output							
Mounting Method:							
Connector							
Terminal Type And Quantity:							
2 connector							
Frequency Range:							
Between 0.000 hertz and 2000.000 megahertz							
Product Name:							
Coaxial precision fixed attenuator							
Shelf Life:							
N/a							

NSN 5985-01-564-6815

Fixed Attenuator - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000