

View Online at <https://aerobasegroup.com/nsn/5985-01-576-3618>

**Application Design:**

Transmission line

**Body Material:**

Aluminum alloy

**Body Style:**

Rectangular, terminal/terminals on opposite surfaces

**Overall Length:**

235.9 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

57.2 millimeters

**Overall Height:**

78.5 millimeters

**Overall Width:**

78.5 millimeters

**Mounting Hole/stud Quantity:**

8

**Unthreaded Mounting Hole Diameter:**

0.138 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

57.2 millimeters

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.10 and 1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

N

**Power Rating:**

250.0 watts average

**Rf Signal Attenuation In Decibels:**

20.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+2.0 gigahertz and +2.0/+5.0 gigahertz

**Mounting Facility Thread Size And Series/type Designator:**

6-32 unc

**Connection Type Per Function:**

Female input and female output

**Mounting Method:**

Threaded hole

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 5.000 gigahertz

**Product Name:**

High power fixed coaxial attenuators

**Special Features:**

Stainless steel connectors; gold plated beryllium copper contacts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A20000