Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-578-4711

## **Application Design:**

Transmission line

#### **Body Material:**

Steel, stainless

## Body Style:

Err-090

## **Overall Length:**

0.760 inches

## **Overall Diameter:**

0.280 inches

## **Operating Tempurature Range:**

-65.0/+125.0 degrees celsius

## Voltage Standing Wave Ratio:

1.15 and 1.35

## Input Impedance Rating In Ohms:

50.0

## **Output Impedance Rating In Ohms:**

50.0

## **Coaxial Connector Series Designation:**

Sma

## **Power Rating:**

2.0 watts average and 250.0 watts peak

## **Rf Signal Attenuation In Decibels:**

0.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

## Attenuation Accuracy In Decibels:

-0.30/+0.30

## **Connection Type Per Function:**

Female input and male output

## **Mounting Method:**

Connector

## **Terminal Type And Quantity:**

2 connector

## Frequency Range:

Between 0.000 gigahertz and 18.000 gigahertz

## **Product Name:**

C attenuators

## Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5985-01-578-4711

Fixed Attenuator - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A20000

