

View Online at <https://aerobasegroup.com/nsn/5985-01-578-5009>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

Err-090

**Overall Length:**

Err-060

**Overall Diameter:**

Err-060

**Operating Temperature Range:**

Err-060

**Voltage Standing Wave Ratio:**

1.15 and 1.35

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

Err-060 average and err-060 peak

**Rf Signal Attenuation In Decibels:**

4.0

**Voltage Standing Wave Ratio Frequency Range:**

Err-060 and err-060 and err-060 and err-060

**Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Connection Type Per Function:**

Err-060 and err-060

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

Err-060

**Frequency Range:**

Err-060 and err-060

**Product Name:**

C attenuators

**Special Features:**

Conductors: gold plated beryllium copper

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000