NSN 5985-01-580-2595

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-580-2595

	- ·
Application	Design:

Transmission line

Body Material:

Aluminum alloy

Body Style:

Irregular

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches

Overall Height:

0.750 inches

Overall Width:

1.250 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Operating Tempurature Range:

-55.0/+100.0 degrees celsius

End Application:

Cabinet, 10 ch low power 9002419-8; wsd: los angeles class ssn (688)

Voltage Standing Wave Ratio:

1.50 and 1.60

Coaxial Connector Series Designation:

Sma

Attenuation Variation Method:

Stepped

Mounting Facility Type And Quantity:

2 unthreaded hole

Frequency Range:

Between 10.000 megahertz and 1000.000 megahertz

Mounting Facility Pattern:

Two position diagonal

Impedance Rating In Ohms:

50.0 input-output

Product Name:

Digital step attenuator

Terminal Type And Quantity:

1 pin and 2 connector, coaxial, female and 5 turret

Shelf Life:

N/a

NSN 5985-01-580-2595

Variable Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0

