## NSN 5985-01-582-4014

Waveguide Assembly - Page 1 of 1



/nsn/5985-01-582-4014

| View Online at https://aerobasegroup.com/nsn/5985-0      |
|--|
| Cross Sectional Shape:                                   |
| Internal, rectangular external, rectangular              |
| Tubing Wall Construction Style:                          |
| Seamless single tubing segment                           |
| Flange Quantity:   |
| 2  |
| Voltage Standing Wave Ratio:                             |
| 1.10   |
| Insertion Loss In Decibels:                              |
| 0.10   |
| Maximum Operating Pressure:                              |
| 60.0 pounds per square inch gage                         |
| Waveguide Inside Width:                                  |
| Between 0.400 inches and 0.900 inches                    |
| Flange Connecting Facility And Quantity:                 |
| 4 unthreaded hole all flanges single connection facility |
| Waveguide Length:  |
| 3.000 inches   |
| Product Name:  |
| Rectangular flexible waveguide                           |
| Specified Frequency:                                     |
| Between 8.2 gigahertz and 12.4 gigahertz                 |
| Flexibility:   |
| Flexible single tubing segment                           |
| Style Designator:  |
| Straight type  |
| Supplementary Features:                                  |
| Waveguide size wr-90                                     |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |

Fiig:

A073a0