NSN 5985-01-590-4792

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-590-4792

C	0	.: 1	Chana.
UIUSS.	340	uonai	Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 all bends e-plane

End Application:

As-4667/wsc- (v)1, as-4670/wsc-9(v), as-4673/wsc-9(v)

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.224 inches all flanges

Flange Inside Height:

0.112 inches all flanges

Flange Outside Width:

0.750 inches all flanges

Flange Outside Height:

0.750 inches all flanges

Flange Depth:

0.188 inches all flanges

Flange Connecting Hole Diameter:

0.133 inches all flanges single connection facility and 0.139 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.15

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Cover type all flanges

Waveguide Length:

1.540 inches

Waveguide Center To Center Distance:

2.377 inches

Product Name:

Inavy-waveguide assembly, q-band controller assembly

Specified Frequency:

Between 43.5 gigahertz and 45.5 gigahertz

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

NSN 5985-01-590-4792

Waveguide Assembly - Page 2 of 2



Sty	υt	-51	u	เลเ	u	I -

Offset bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0