# NSN 5985-01-596-9559

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-596-9559

## **Body Style:**

1b round, terminal/terminals in opposite surface

## **Overall Length:**

0.860 inches

## **Operating Tempurature Range:**

-65.0 to 125.0 degrees celsius

## Voltage Standing Wave Ratio:

1.15 and 1.20 and 1.25 and 1.35 and 1.40

## Input Impedance Rating In Ohms:

50.0

### **Coaxial Connector Series Designation:**

Sma

Power Rating:

### 250.0 watts peak

**Rf Signal Attenuation In Decibels:** 

2.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0 to 4.0 gigahertz and +4.0 to 8.0 gigahertz and +8.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz and +18.0 to 23.0 gigahertz

## **Connection Type Per Function:**

Male input and female output

## Terminal Type And Quantity:

2 connector

### **Frequency Range:**

Between 0.0 gigahertz and 23.0 gigahertz

### **Special Features:**

Gold plated berlyium copper conductors

### **Precious Material And Location:**

Conductor surface gold

### **Precious Material:**

Gold

### Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

No

## Fiig:

A20000