

View Online at <https://aerobasegroup.com/nsn/5985-01-600-0159>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b second flange all connection facilities

**Thread Direction:**

Right-hand all flanges all connection facilities

**End Application:**

Next assembly and used on 200532017

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Voltage Standing Wave Ratio:**

1.20

**Insertion Loss In Decibels:**

0.10

**Thready Qty Per Inch (tpi):**

20 all flanges all connection facilities

**Maximum Operating Pressure:**

25.0 pounds per square inch gage

**Thread Size:**

0.250 inches all flanges all connection facilities

**Flange Connecting Facility And Quantity:**

8 threaded hole all flanges all connection facilities

**Flange Style:**

Cover type first flange

**Waveguide Length:**

51.000 inches

**Waveguide Center To Center Distance:**

20.750 inches

**Specified Frequency:**

Between 3.95 gigahertz and 5.85 gigahertz

**Special Features:**

Flange type: cpr-187 (0.375 in. Thk), 1x cover, w/stainless steel captive fasteners, hex socket head (accurate screw part no. 114121-1.250ssm7-12 or equivalent); 1x grooved contact w/helicoil inserts; wr-187 flexguide w/protective elastomeric coating; 1.0mw peak power handling, 1.0kw avg power handling; operating temp: -40/+52 degrees c, storage temp: -40/+68 degrees c.

**Flexibility:**

Flexible all tubing segment or rigid all tubing segment

**Material:**

Aluminum all tubing segment and flange

**Style Designator:**

Offset bend type

**Thread Series Designator:**

Unc all flanges all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0