

View Online at <https://aerobasegroup.com/nsn/5985-01-600-0445>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

End Application:

Next assembly and used on 200532017

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Voltage Standing Wave Ratio:

1.25

Insertion Loss In Decibels:

0.40

Thready Qty Per Inch (tpi):

20 all flanges all connection facilities

Maximum Operating Pressure:

25.0 pounds per square inch gage

Thread Size:

0.250 inches all flanges all connection facilities

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

69.520 inches

Specified Frequency:

Between 6.30 gigahertz and 6.75 gigahertz

Special Features:

Flange type: 2x cpr-159 cover, w/stainless steel captive fasteners, hex socket head (accurate screw part no. 114121-1.250ssm7-12 or equivalent), wr-159 flexguide w/heavy wall (0.125 in.), w/protective elastomeric coating, both ends; 1mw peak power handling, 1.0kw avg. Power handling; operating temp: -40/+52 degrees c, storage temp: -40/+68 degrees c.

Flexibility:

Flexible all tubing segment or rigid all tubing segment

Material:

Copper alloy all flange

Style Designator:

Offset bend type

Thread Series Designator:

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0