

View Online at <https://aerobasegroup.com/nsn/5985-01-600-0683>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

End Application:

Next assemblies 200425585 and 200532019 used on 200532017

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Voltage Standing Wave Ratio:

1.18

Insertion Loss In Decibels:

0.10

Thready Qty Per Inch (tpi):

20 all flanges all connection facilities

Maximum Operating Pressure:

40.0 pounds per square inch gage

Thread Size:

0.250 inches all flanges all connection facilities

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Flange Style:

Cover type first flange

Waveguide Length:

11.750 inches

Waveguide Center To Center Distance:

3.750 inches

Specified Frequency:

Between 4.9 gigahertz and 6.75 gigahertz

Special Features:

Flange type: cpr-159 1x cover w/stainless steel captive fasteners, socket head, 1.25 lg, 0.483 thread length; 1x grooved contact w/threaded inserts; wr-159 w/heavy wall (0.125 in.) rigid, w/protective elastomer coating, internal walls of the flexible waveguide shall be silver plated; 1.0mw peak power handling, 1.0kw avg power handling; operating temp: -40/+52 degrees c, storage temp: -40/+68 degrees c.

Flexibility:

Flexible all tubing segment or rigid all tubing segment

Material:

Copper single tubing segment

Style Designator:

Offset bend type

Thread Series Designator:

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0