

View Online at <https://aerobasegroup.com/nsn/5985-01-600-0714>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

End Application:

Next assembly 200425797 used on 200532017

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Voltage Standing Wave Ratio:

1.25

Insertion Loss In Decibels:

0.10

Thready Qty Per Inch (tpi):

20 all flanges all connection facilities

Maximum Operating Pressure:

40.0 pounds per square inch gage

Thread Size:

0.250 inches all flanges all connection facilities

Waveguide Longer Offset Distance:

10.540 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Flange Style:

Cover type first flange

Waveguide Offset Distance:

6.590 inches

Specified Frequency:

Between 4.9 gigahertz and 6.75 gigahertz

Special Features:

Flange type: cpr159f modified w/stainless steel captive hardware 1.25 lg socket head cap screw and cpr159g; wr159 flexible waveguide w/silicon jacket; 1.0mw peak power handling, 1.0kw avg. Power handling; operating temp: -40/+52 degrees c, storage temp: -40/+68 degrees c.

Flexibility:

Flexible single tubing segment

Material:

Copper single tubing segment

Style Designator:

Bend type

Thread Series Designator:

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0