NSN 5985-01-600-5053

Waveguide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-600-5053

Overall Length:				
15.750 inches				
Overall Height:				
9.500 inches				
Overall Width:				
9.500 inches				
Frequency Rating:				
1.12 gigahertz single frequency operating and 1.70 gigahertz single frequency operating				
Switch Type:				
Transfer				
Distance Between Mounting Facility Centers:				
8.000 inches single mounting facility pattern				
Voltage Standing Wave Ratio:				
1.05 single				
Insertion Loss In Decibels:				
0.01 single				
Actuator Operating Method:				
Manual				
Actuator Current Type And Rating In Amps:				
5.0 ac				
Actuator Voltage In Volts:				
Between 22.0 and 32.0				
Switch Operation Sequence:				
Makes before breaks				
Switching Time:				
1.0 seconds				
Switch Return Mechanism Type:				
Latching				
Pole Quantity:				
1				
Throw Quantity:				
2				
Mounting Facility Type And Quantity:				
4 threaded hole				
Mounting Facility Pattern:				
Four position rectangular single mounting facility pattern				
Flange Connecting Facility And Quantity:				
10 unthreaded hole				

Special Features:

Wr650 waveguide switch, I-band, mini-series

Product Name:

80db min isolation; pressure to 30 psig (r-f head); iridite on flange faces; metric thread, (m8x1.25 x 12mm inserts, metric sw) wr650 flange (cprf); mounting: 4x m12x1.75x18mm lg inserts on metric sw

NSN 5985-01-600-5053

Waveguide Switch - Page 2 of 2



N/	late	ria	
IV	alt	:110	и.

Aluminum flang (s)

Surface Treatment:

Enamel body outside surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0