

View Online at <https://aerobasegroup.com/nsn/5985-01-600-6713>

Application Design:

Transmission line

Body Style:

1b round, terminal/terminals in opposite surface

Overall Length:

2.250 inches

Overall Diameter:

1.000 inches

Voltage Standing Wave Ratio:

1.15 and 1.20 and 1.25 and 1.35

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

N

Power Rating:

1.0 watts peak

Rf Signal Attenuation In Decibels:

20.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz and +12.0/+18.0 gigahertz

Attenuation Accuracy Reference Frequency:

18.0 gigahertz

Attenuation Accuracy In Decibels:

-1.00/+1.00

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Product Name:

Low voltage attenuator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A20000